



Porsche - Supplement Install Guide

Use this guide in addition to the blip module install manual.


Note pictures and OEM wire colors are from 981 Boxster/Cayman

Prepare for installing the blip module in or near the glove box

- Ground: Any Vehicle Ground ran to the glove box location
- 12V Power: Any Switched 12V power Source ran to the glove box location thru a switch
- Clutch Signal: Pin 17 on DME connector A (WHT) - Active LOW on pedal press
- Brake Signal: Pin 3 on Brake pedal switch (GRN/RED) - Active High on pedal press
- Throttle: Plug and Play Pedal harness.

Pedal Harness

1. Carefully remove OEM pedal by removing single bolt T25, gently slide the pedal UP to remove. Push down the grey tab while pulling the connector off the pedal, it will be tight.
2. Connect the Xineering pedal harness to the vehicle connector (F) and the pedal (M).
3. Reinstall the pedal and bolt.
4. Pass the throttle pedal harness and brake signal wire (Blip BRN) behind the console from the passenger side foot well to the driver side foot well.



Clutch Signal - FIG 1

Clutch - DME Located in the Right Side of the rear compartment.

Pin 17 - WHT Connect to Blip module YEL

1. Unwrap the loom tape on DME connector A (Smaller)
2. Tap the White signal wire as shown in Fig 1.

Brake Signal - FIG 2

Brake - Stop Light Switch on brake pedal linkage harness located above throttle pedal assembly.

Active High on pedal press, 0.6V unpressed.

Pin 3 - GRN/RED Connect to **Blip Module BRN** wire

Brake Pedal Switch harness can be followed toward the center of the car, shown unwrapped above the throttle pedal in Fig 2.

1. Unwrap the loom tape
2. Tap the GRN/RED signal wire

FIG 1 - Clutch Signal at DME



FIG 2 - Brake Switch over pedal

